

NSF International

789 N. Dixboro Road, Ann Arbor, MI 48105 USA

RECOGNIZES

Danfoss

Facility: Nuevo León, Mexico

AS COMPLYING WITH NSF/ANSI/CAN 61, NSF/ANSI/CAN 372 AND ALL APPLICABLE REQUIREMENTS. PRODUCTS APPEARING IN THE NSF OFFICIAL LISTING ARE AUTHORIZED TO BEAR THE NSF MARK.



This certificate is the property of NSF International and must be returned upon request. This certificate remains valid as long as this client has products in NSF's Official Listings for the referenced standards. For the most current and complete Listing information, please access NSF's website (www.nsf.org).

A handwritten signature in black ink, appearing to read "Nasrin Kashefi".



OFFICIAL LISTING

NSF Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI/CAN 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on August 07, 2025.

Danfoss
Nordborgvej 81
DK-6430 Nordborg
Denmark
45 74 88 22 22

Facility: Nuevo León, Mexico

Mechanical Devices

Trade Name	Size	Water Contact Temp	Water Contact Material
Transmitters/Gauges [G] DST Plxx	[1]	C. HOT	SS

[1] The 'xx' in the trade name is used as an ordering code for each pressure connector variant.

Certified for the following pressure connectors:

- 1/2-14 NPT, ANSI/ASME B1.20.1
- G1/2 - EN837
- 1/8-27 NPT, ANSI/ASME B1.20.1
- 1/4-18 NPT, ANSI/ASME B1.20.1
- R 1/4 ISO 7-1
- 7/16-20 UNF-2B
- 1/8-27 NPTF
- 1/4-18 NPTF
- 1/4-18 NPT-4mm inlet hole
- G 1/4A - EN837
- 1/4-18 NPT - AISI 316L
- G1/2 - EN837 - AISI 316L

[G] Product is Certified to NSF/ANSI/CAN 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Facility: Tianjin, China

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



Mechanical Devices

Trade Name	Size	Water Contact Temp	Water Contact Material
Switches/Sensors [G]			
DST P3XX	[1]	C. HOT	SS
MBS 3XXX	[1]	C. HOT	SS
Transmitters/Gauges [G]			
DST P1xx	[2]	C. HOT	SS

[1] The 'xx' in the trade name is used as an ordering code for each pressure connector variant. Certified for the following pressure connectors:

- 1/2-14NPT Ø4,2 HEX27
- 1/2-14NPT Ø10 HEX27
- 1/2-14NPTF Ø15 HEX27
- 1/4-18NPT Ø4,2 HEX27
- 1/4-18NPT M5 HEX27
- 1/4-18NPTF Ø4,2 HEX25,4
- 1/4-18NPTF M5 HEX25,4
- 1/8-27NPT Ø3,3 HEX25,4
- 1/8-27NPT Ø3,3 HEX27
- 7/16-20UNF Ø4,2 HEX27
- R1/4 M5 HEX27
- R3/8 M5 HEX27
- G1/2A Ø4,2 HEX27
- G1/2 HEX27
- M5 G1/4A Ø3,3 HEX27
- G3/8A Ø4,2 HEX27
- G3/8A M5 HEX27
- M20x1.5 HEX27 M5

[2] The "xx" in the trade name is used as an ordering code for each pressure connector variant. Certified for the following pressure connectors:

- 1/2-14 NPT, ANSI/ASME B1.20.1
- G 1/4A - EN837
- G1/2 - EN837
- G 1/2- EN837- AISI 316L
- 1/8-27 NPT, ANSI/ASME B1.20.1
- 1/4-18 NPT - AISI 316L
- 1/4-18 NPT, ANSI/ASME B1.20.1
- R 1/4 ISO 7-1
- 7/16-20 UNF-2B
- 1/8-27 NPTF
- 1/4-18 NPTF
- 1/4-18 NPT-4mm inlet hole

[G] Product is Certified to NSF/ANSI/CAN 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



OFFICIAL LISTING

NSF Certifies that the products appearing on this Listing conform to the requirements of
NSF/ANSI/CAN 372 - Drinking Water System Components - Lead Content

This is the Official Listing recorded on August 07, 2025.

Danfoss
Nordborgvej 81
DK-6430 Nordborg
Denmark
45 74 88 22 22

Facility: Nuevo León, Mexico

Transmitters/Gauges [LL]

DST Plxx [1]

[1] The 'xx' in the trade name is used as an ordering code for each pressure connector variant.

Certified for the following pressure connectors:

1/2-14 NPT, ANSI/ASME B1.20.1
G1/2 - EN837
1/8-27 NPT, ANSI/ASME B1.20.1
1/4-18 NPT, ANSI/ASME B1.20.1
R 1/4 ISO 7-1
7/16-20 UNF-2B
1/8-27 NPTF
1/4-18 NPTF
1/4-18 NPT-4mm inlet hole
G 1/4A - EN837
1/4-18 NPT - AISI 316L
G1/2 - EN837 - AISI 316L

[LL] Product conforms with lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Facility: Tianjin, China

Switches/Sensors [LL]

DST P3XX [1]

MBS 3XXX [1]

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



Transmitters/Gauges [LL]

DST Plxx [2]

[1] The 'xx' in the trade name is used as an ordering code for each pressure connector variant. Certified for the following pressure connectors:

1/2-14NPT Ø4,2 HEX27
1/2-14NPT Ø10 HEX27
1/2-14NPTF Ø15 HEX27
1/4-18NPT Ø4,2 HEX27
1/4-18NPT M5 HEX27
1/4-18NPTF Ø4,2 HEX25,4
1/4-18NPTF M5 HEX25,4
1/8-27NPT Ø3,3 HEX25,4
1/8-27NPT Ø3,3 HEX27
7/16-20UNF Ø4,2 HEX27
R1/4 M5 HEX27
R3/8 M5 HEX27
G1/2A Ø4,2 HEX27
G1/2 HEX27
M5 G1/4A Ø3,3 HEX27
G3/8A Ø4,2 HEX27
G3/8A M5 HEX27
M20x1.5 HEX27 M5

[2] The "xx" in the trade name is used as an ordering code for each pressure connector variant. Certified for the following pressure connectors:

1/2-14 NPT, ANSI/ASME B1.20.1
G 1/4A - EN837
G1/2 - EN837
G 1/2- EN837- AISI 316L
1/8-27 NPT, ANSI/ASME B1.20.1
1/4-18 NPT, ANSI/ASME B1.20.1
1/4-18 NPT - AISI 316L
R 1/4 ISO 7-1
7/16-20 UNF-2B
1/8-27 NPTF
1/4-18 NPT-4mm inlet hole
1/4-18 NPTF

[LL] Product conforms with lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.